



# TermiCom SE-15




Totally sealed computer with very good performance for industrial environments. The base configuration is a color LCD screen TFT 15 inch resistive touch screen and a VIA Eden 800 MHZ processor. A Teflon tip pen is available to point precisely on the touch screen. In option, you can order a WiFi 802.11b RF network interface. The sturdy stainless steel case for industrial environments (totally sealed) can be wash down.



Below View



Technology allows you to use a standard USB connectors!



The stand provided with the SE TermiCom can be used in a wallmount or desktop position. Once fixed, the angle of the TermiCom can be easily adapted to the needs of each user. In option, you can add a stainless steel keyboard shelf. Many ports are available to connect peripherals like, industrial keyboard, barcode reader, proximity reader, etc ... You can protect the Flash drive completely to prevent deleting or modifying the operating system or your application.





Wallmount Position



Desktop Position

## General characteristics

# TermiCom XPe

<b>Processor :</b>	 Low power consumption VIA Eden 800 Mhz
<b>Memory:</b>	256 Megs (default) up to maximum 512 Megs RAM
<b>Hardisk:</b>	512 Megs Flash disk minimum ( <i>non mechanical</i> )
<b>Screen:</b>	Color 24 bits LCD TFT (1024 X 768) SVGA, 15 inch touch screen resistive ( <i>by pressure</i> )
<b>Input/Output:</b>	3 serial ports (Optional) 2 USB ports 1 Ethernet port 10/100 BaseT,
<b>Operating System:</b>	 (Microsoft © Windows © XP Embedded)
<b>Stand:</b>	Tilt stand that can be Wallmount or Desktop.
<b>Limited Warranty:</b>	1 year parts and labor in workshop ( <i>Extended warranty available</i> ).

## Physical characteristics

<b>Weight :</b>	Approx. 13.6 kg (30 pounds) without options
<b>Power :</b>	120/240 VAC 60/50 HZ
<b>Case :</b>	Stainless Steel

## Others

<b>Options :</b>	Barcode reader : pen, CCD, laser, etc. Slot reader Industrial Waterproof Keyboard Keyboard stand Proximity reader Printers Etc ...
------------------	--

## Environment

<b>Operating temperature:</b>	5° to 40°C
<b>Storage temperature:</b>	-20° to 60°C
<b>Relative humidity:</b>	100%

