

# *NEMA 4 Enclosure*

## For Wireless Access Points



### *Outdoor protection for access points*

The LXE NEMA 4 Enclosure enables Network Planners to extend their 802.11b wireless local area networks (WLAN) into harsh indoor or outdoor environments. The NEMA 4 Enclosure protects your access point and wireless bridge from environmental hazards such as rain, snow, ice, hose spray, dust and wind-blown sand. And, with an optional heater, the LXE NEMA 4 Enclosure allows operation of a wireless network in extreme cold, including food processing facilities and freezers.

Constructed of entirely non-corrosive components, the NEMA 4 Enclosure is perfect for shipping and trans-modal ports and in outdoor storage yards.

### *Extend the LAN beyond Ethernet cabling*

The LXE NEMA 4 Enclosure can be configured to accept both an access point and a wireless bridge. This allows an enterprise to effectively extend their LAN to outdoor locations that are not reached by the Ethernet cabling. The wireless bridge provides the backbone connection to a corresponding wireless bridge unit that has Ethernet access to the LAN. The co-located access point provides an 802.11 cell of coverage for connecting wireless computers to the network.

### *Flexible installation options*

The LXE NEMA 4 is designed for easy installation on either walls or on light poles and is available in optional configurations that accommodate a variety of popular WLAN access points and wireless bridges.

To make installation even easier, the LXE NEMA 4 Enclosure, with an installed 'Power over Ethernet' enabled access point, does not require AC power.



# NEMA 4 ENCLOSURE For WLAN Access Points

## TECHNICAL SPECIFICATIONS

### Model Number

NEMA4AM

### Access Points Supported

Cisco AIR-AP352E2R-x-K9 (LXE Model 6720)  
Cisco AIR-AP1220B-x-K9 (LXE Model 6730)  
Cisco AIR-AP1230B-x-K9 (LXE Model 6730)  
Proxim AP1000 (LXE Model 6520)  
Proxim AP2000  
Proxim AP600 (LXE Model 6540)

### Wireless Bridges Supported

Cisco AIR-BR350-x-K9 (LXE Model 6723)  
Proxim MP.11 (LXE Model 6543)

### Environmental

Operating Temperature:  
With heater: -22°F (-30°C) to 122°F (50°C)  
Without heater: 32°F (0°C) to 122°F (50°C)  
NEMA 4 rated for water intrusion

### Physical

Dimensions:  
22.0 in. x 13.3 in. x 4.0 in.  
(559mm x 337mm x 103mm)  
Weight (with LXE 6720 access point):  
14.8 lbs. (6.71kg)

### Electrical

120 VAC, 50-60 Hz  
8 watts maximum without heater  
270 watts maximum with heater  
240 VAC, 50-60 Hz  
9 watts maximum without heater  
300 watts maximum with heater

### Enclosure

Painted Aluminum for corrosion resistance  
Stainless steel latches

### Package Contents

Environmental enclosure  
Mounting hardware for selected access point  
and/or bridge  
AC heater (optional)

### Accessories

Access point mounting kits  
Lightning surge suppression for antennas  
AC Power surge suppression  
Ethernet surge suppression



Copyright © 2002-04 LXE Inc. All rights reserved. Specifications are subject to change without notice. All names, products, and services mentioned are the trademarks or registered trademarks of their respective organizations. Datalight is a trademark of Datalight, Inc. ROM-DOS is a trademark of Datalight, Inc. Portions © GPVNO.BK

DS0204-MX1\_Web

125 Technology Parkway

Norcross, GA 30092

770-447-4224

www.lxe.com

